

# SPORTABLE SCOREBOARDS®


## SCOREBOARD SPECIFICATIONS FOR



### MODEL 3430LED

[www.sportablescoreboards.com](http://www.sportablescoreboards.com)

Sportable Scoreboards  
106 Max Hurt Drive  
Murray, KY 420071  
Phone: 800-323-7745 Fax: 270-759-4112  
[www.sportablescoreboards.com](http://www.sportablescoreboards.com)



## SCOREBOARD SPECIFICATIONS

## MODEL 3430LED

Lead your TEAM with this SOCCER scoreboard! Large 15" high super-bright 100,000-hour rated LED numerals are the largest with the widest viewing angle in the industry and are visible over 300 feet. The 22-gauge galvanized steel cabinet with powder-coat finish means your scoreboard is the most durable on the market and will look brand new for many years! Scoreboard package includes: operator's keyboard, digit protective shields, junction box cover (cable models only), mounting rails and a complete operation, installation, service manual and warranty details are included on the CD shipped with each scoreboard.

### OVERALL DIMENSIONS

8' wide x 4' tall x 8.0" depth

### WEIGHT

Hanging weight: 180 lbs.  
Shipping weight: 235 lbs.

### CONSTRUCTION

22-gauge galvanized steel cabinet with powder coat finish for strength, durability, and lasting appearance

### POWER REQUIREMENTS

#### **Scoreboard:**

(1) 20-amp, 120-volt, 60-hertz, grounded AC circuit connected to an ON/OFF switch and/or circuit breaker

#### **Controller:**

Standard LCD controller powered by 12V DC Adapter or an optional internal battery.

### SCORING INFORMATION DISPLAYED

**HOME:** 2-digit displays, 0-99

**GUEST:** 2-digit display, 0-99

**PERIOD:** 1-digit display, 0-9

**GOAL:** 2 – 2.0" dot display

**CLOCK:** 4 – digit display, 00-99

### CAPTIONS

**HOME, GUEST:** 6.0" tall

**PERIOD:** 3.5" tall

**GOAL:** 3.25" tall

**CLOCK COLON:** 2.0" tall

### HOME, GUEST, CLOCK and PERIOD Displays

15.0" tall, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays  
**Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included**

### GOAL Displays

2.0" dot indicators, 160° visibility, red, 100,000 hour-rated, outdoor Super-Bright LED (light emitting diode) displays

**Impact Resistant Acrylic Protective Digit Shields and Adjustable LED Intensity Included**

### APPROVALS

ETL/CSA listed

**Scoreboard:** Meets all FCC Class A requirements

**900 MHz wireless transmitter:** FCC Part 15 certified

**900 MHz wireless receiver:** Meets all FCC Part 15 requirements

## **WARRANTY**

This product is warranted against defects in materials and workmanship for the period specified in the warranty from the date of invoice. The complete warranty details are included on the CD shipped with each unit.

## **SERVICE**

Technical Support is available 24 hours a day, 7 days a week @ 1-800-411-3136

## **INSTALLATION**

This model may be installed between (2) 8" OD steel, schedule 40 poles; or (2) 8" I-beams, minimum. Hole depth /diameter as well as pole/concrete specifications must be based on customer's local building codes, soil conditions, and wind loads. Mounting rails are supplied.

***Support structure and mounting hardware supplied by installer/others***

## **SCOREBOARD CONTROLLER**

**Dimensions:** 2.5" height x 14.0" width x 7.0" depth. **Weight:** 2.10 lbs.

The keyboard controller available with this scoreboard is microprocessor-controlled, molded of high-impact ABS plastic, has a tactile membrane keypad. Options include 900 MHz wireless control and internal battery pack with automatic battery charger.

### **Cable-Controlled System (standard) Includes:**

- (1) Keyboard controller
- (3) SOCCER keypad inserts
- (1) Junction box cover with receptacle (to be installed at scorekeeper's location)
- (1) 20-ft. signal cable (used to connect the keyboard to the junction box receptacle)
- (1) Project-specific length of 4 wire twisted pair, shielded control cable

### **900 MHz Wireless System (optional) Includes:**

- (1) Universal LCD keyboard controller (internal battery pack with built-in charger)
- (3) SOCCER keypad inserts
- (1) 12-volt DC wall transformer
- (1) 900 MHz transmitter (connects to keyboard controller via supplied interface cable)
- (1) 900 MHz receiver (connects to the scoreboard, eliminating control cable and junction box installation) (to be installed at scorekeeper's location)

## **OPTIONS**

See Sportable Scoreboards catalog #67 for full list of options

Scoreboard Dimensions:  
4' tall x 8' wide x 8.0" depth

