

## 1. Identification

**Product identifier** AMERI-STRIPE WHITE FIELD MARKING PAINT

### Other means of identification

**Product Code** 08670 107832 713

**Recommended use** Not available.

### Manufacturer/Importer/Supplier/Distributor information

**Company name** Quest Industrial Products, LLC.  
**Address** N92 W14701 Anthony Avenue  
 Menomonee Falls, WI 53051  
 United States  
**Telephone** General Assistance (262) 255-9500  
**Website** quest-ip.com  
**E-mail** info@quest-ip.com  
**Emergency phone number** Chemtrec Phone 800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 2  
 Gases under pressure Liquefied gas  
**Health hazards** Acute toxicity, oral Category 4  
 Serious eye damage/eye irritation Category 2A  
 Carcinogenicity Category 2  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Warning

**Hazard statement** Flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes serious eye irritation. Suspected of causing cancer.

### Precautionary statement

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If swallowed: Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Rinse mouth. If eye irritation persists: Get medical advice/attention.

**Storage** Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** 43.61% of the mixture consists of component(s) of unknown acute oral toxicity.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
ETHYL ACETATE		141-78-6	10 to <20
PROPANE		74-98-6	10 to <20
CALCIUM CARBONATE		1317-65-3	5 to <10
TITANIUM DIOXIDE		13463-67-7	5 to <10
MINERAL SPIRITS		64741-65-7	1 to <5
N-BUTANE		106-97-8	1 to <5
PETROLEUM NAPHTHA		8032-32-4	1 to <5
Other components below reportable levels			50 to <60

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Not likely, due to the form of the product. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
<b>Most important symptoms/effects, acute and delayed</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

## Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

## Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
CALCIUM CARBONATE (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
ETHYL ACETATE (CAS 141-78-6)	PEL	1400 mg/m3	
MINERAL SPIRITS (CAS 64741-65-7)	PEL	400 ppm	
		400 mg/m3	
PROPANE (CAS 74-98-6)	PEL	100 ppm	
		1800 mg/m3	
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	1000 ppm	
		15 mg/m3	Total dust.

#### US. ACGIH Threshold Limit Values

Components	Type	Value
ETHYL ACETATE (CAS 141-78-6)	TWA	400 ppm
N-BUTANE (CAS 106-97-8)	STEL	1000 ppm
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
CALCIUM CARBONATE (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
ETHYL ACETATE (CAS 141-78-6)	TWA	10 mg/m3 1400 mg/m3	Total
MINERAL SPIRITS (CAS 64741-65-7)	TWA	400 ppm 400 mg/m3	
N-BUTANE (CAS 106-97-8)	TWA	100 ppm 1900 mg/m3	
PETROLEUM NAPHTHA (CAS 8032-32-4)	Ceiling	800 ppm 1800 mg/m3	
PROPANE (CAS 74-98-6)	TWA TWA	350 mg/m3 1800 mg/m3 1000 ppm	

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

For prolonged or repeated skin contact use suitable protective gloves.

**Other**

Wear suitable protective clothing.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Aerosol. Liquefied gas.

**Color**

Not available.

**Odor**

Not available.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

-305.68 °F (-187.6 °C) estimated

**Initial boiling point and boiling range**

-43.78 °F (-42.1 °C) estimated

**Flash point**

201.0 °F (93.9 °C) estimated

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not applicable.

**Upper/lower flammability or explosive limits****Flammability limit - lower (%)**

2.4 % estimated

**Flammability limit - upper (%)**

9.5 % estimated

**Explosive limit - lower (%)**

Not available.

<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	1795.71 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	800 °F (426.67 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	7.71 lbs/gal
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Flammable IA estimated
<b>Heat of combustion (NFPA 30B)</b>	10.58 kJ/g estimated
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	79.89
<b>Specific gravity</b>	0.93
<b>VOC</b>	4.88 lbs/gal Regulatory 585.21 g/l Regulatory 3.07 lbs/gal Material 367.51 g/l Material

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Acids. Strong oxidizing agents. Nitrates. Fluorine.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Harmful if swallowed.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
---	---

### Information on toxicological effects

<b>Acute toxicity</b>	Harmful if swallowed.
-----------------------	-----------------------

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
ETHYL ACETATE (CAS 141-78-6)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Rat	16000 ppm, 6 Hours
LD50	Mouse	1500 ppm, 4 Hours
	Rabbit	2500 ppm, 4 Hours

Components	Species	Test Results
	Rat	4000 ppm, 4 Hours
<b>Oral</b>		
LD50	Mouse	0.44 g/kg
	Rabbit	4.9 g/kg
	Rat	11.3 ml/kg
		5.6 g/kg
MINERAL SPIRITS (CAS 64741-65-7)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Rat	61 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 25 ml/kg
N-BUTANE (CAS 106-97-8)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
PETROLEUM NAPHTHA (CAS 8032-32-4)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Rat	3400 mg/l, 4 Hours
PROPANE (CAS 74-98-6)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
TITANIUM DIOXIDE (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not regulated.	
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>	
Not listed.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

### Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
ETHYL ACETATE (CAS 141-78-6)		
<b>Aquatic</b>		
Fish	LC50	Indian catfish (Heteropneustes fossilis) 200.32 - 225.42 mg/l, 96 hours
MINERAL SPIRITS (CAS 64741-65-7)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 8.8 mg/l, 96 hours
		8.8 mg/l, 96 hours
TITANIUM DIOXIDE (CAS 13463-67-7)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

### Persistence and degradability

No data is available on the degradability of this product.

### Bioaccumulative potential

#### Partition coefficient n-octanol / water (log Kow)

ETHYL ACETATE	0.73
N-BUTANE	2.89
PROPANE	2.36

### Mobility in soil

No data available.

### Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

### Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

### Local disposal regulations

Dispose in accordance with all applicable regulations.

### Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

### Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

### Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## 14. Transport information

### DOT

UN number	UN1950
UN proper shipping name	UN1950, Aerosols, Flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

**IATA**

UN number	UN1950
UN proper shipping name	Aerosols, Flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

**IMDG**

UN number	UN1950
UN proper shipping name	Aerosols, Flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code  
Not established.

**DOT**



**IATA; IMDG**



**General information**

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

### **CERCLA Hazardous Substance List (40 CFR 302.4)**

ETHYL ACETATE (CAS 141-78-6)	Listed.
N-BUTANE (CAS 106-97-8)	Listed.
PROPANE (CAS 74-98-6)	Listed.

### **SARA 304 Emergency release notification**

Not regulated.

### **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not regulated.

### **Superfund Amendments and Reauthorization Act of 1986 (SARA)**

<b>Hazard categories</b>	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

### **SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

### **SARA 313 (TRI reporting)**

Not regulated.

### **Other federal regulations**

#### **Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

#### **Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

#### **FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

ETHYL ACETATE (CAS 141-78-6)	Low priority
------------------------------	--------------

### **US state regulations**

#### **US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

#### **US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

MINERAL SPIRITS (CAS 64741-65-7)
N-BUTANE (CAS 106-97-8)
PETROLEUM NAPHTHA (CAS 8032-32-4)
TITANIUM DIOXIDE (CAS 13463-67-7)

#### **US. Massachusetts RTK - Substance List**

CALCIUM CARBONATE (CAS 1317-65-3)
ETHYL ACETATE (CAS 141-78-6)
MINERAL SPIRITS (CAS 64741-65-7)
N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)
TITANIUM DIOXIDE (CAS 13463-67-7)

#### **US. New Jersey Worker and Community Right-to-Know Act**

CALCIUM CARBONATE (CAS 1317-65-3)
ETHYL ACETATE (CAS 141-78-6)
N-BUTANE (CAS 106-97-8)
PETROLEUM NAPHTHA (CAS 8032-32-4)
PROPANE (CAS 74-98-6)
TITANIUM DIOXIDE (CAS 13463-67-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

CALCIUM CARBONATE (CAS 1317-65-3)  
ETHYL ACETATE (CAS 141-78-6)  
MINERAL SPIRITS (CAS 64741-65-7)  
N-BUTANE (CAS 106-97-8)  
PETROLEUM NAPHTHA (CAS 8032-32-4)  
PROPANE (CAS 74-98-6)  
TITANIUM DIOXIDE (CAS 13463-67-7)

**US. Rhode Island RTK**

ETHYL ACETATE (CAS 141-78-6)  
N-BUTANE (CAS 106-97-8)  
PROPANE (CAS 74-98-6)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)	Listed: October 1, 1988
TITANIUM DIOXIDE (CAS 13463-67-7)	Listed: September 2, 2011

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

Issue date	05-24-2016
Revision date	08-21-2018
Version #	06
HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0

Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.
------------	---