



Digit Size: 14"/18" **Digit Color:** High Intensity Red ,Amber, or Translucent White

BALL 3		STRIKE 2		OUT 2							
NEVCO		1	2	3	4	5	6	7	8	9	TOTAL
TIGERS		0	0	0	0	0	0	0	0	0	0
KNIGHTS		2	3	0	0	0	0	0	4	4	0

SHOWN WITH OPTIONAL ELECTRONIC TEAM NAMES

***Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard**

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360
FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 1608 (Outdoor) Baseball/Softball Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 1608	MPC WIRED	MPCW WIRELESS	MPCX ₂ WIRELESS
LINE SCORES 14" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9 for nine (9) innings.	Displays 0-9 for nine (9) innings.	Displays 0-9 for nine (9) innings.
RUNS 14" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99. Total runs accumulate for up to 27 innings as each inning score is entered.	Displays 0-99. Total runs accumulate for up to 27 innings as each inning score is entered.	Displays 0-99. Total runs accumulate for up to 19 innings as each inning score is entered.
BALL 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9.	Displays Blank-9.	Displays Blank-9.
STRIKE 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9.	Displays Blank-9.	Displays Blank-9.
OUT 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9.	Displays Blank-9.	Displays Blank-9.
PITCH COUNT	N/A	Supported. Integrates with PCD display. Controlled by hand-held switches.	Supported. Integrates with PCD display. Requires Pitch Count MPCX ₂ control.
PITCH TIMER	N/A	Supported. Integrates with 9520 display. Controlled by hand-held switches.	Supported. Integrates with 9520 display. Requires SCD/DGT MPCX ₂ control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 18'L x 6'H x 8"D (5.49 x 1.83 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Hanging weight approximately 320 lbs. (145 kg) or 375 lbs. (170 kg) with ETNs.

CAPTIONS: HOME, GUESTS, BALL, STRIKE, OUT, white letters 10" high. All other captions white letters 8" high. (HOME and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

POWER WITHOUT ETNS (RED/AMBER): 120 VAC, 2.0 Amps, 50/60 Hz. / 240 VAC, 1.0 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (RED/AMBER): 120 VAC, 2.5 Amps, 50/60 Hz. / 240 VAC, 1.3 Amps, 50/60 Hz. Requires earth ground.

POWER WITHOUT ETNS (TRANSLUCENT WHITE): 120 VAC, 3.3 Amps, 50/60 Hz. / 240 VAC, 1.6 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (TRANSLUCENT WHITE): 120 VAC, 4.4 Amps, 50/60 Hz. / 240 VAC, 2.2 Amps, 50/60 Hz. Requires earth ground.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION/

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM