





CUSTOMIZE "HOME" AND "GUESTS" BY UPGRADING TO ELECTRONIC TEAM NAMES. MODEL ABOVE SHOWN WITH ALL WHITE DIGITS UPGRADE.

Advanced timing features ideal for Basketball/ Volleyball/Wrestling Facilities.

- Energy-efficient LEDs reduce power consumption and operating expense.
- Ability to retrofit team name caption plates.
- Bright, long lasting LED lamp banks when ordered with rear-lit team names.
- Large, 4" Bonus, Double Bonus and Possession Indicator digits included.
- Durable and lightweight cabinet design.
- Universal—syncs with Nevco accessories.
- Extended advertising opportunities.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- Built-in Power Factor Correction.



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT: WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 2700 (Indoor) Basketball/Volleyball/Wrestling Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 2700	MPC WIRED	MPCW WIRELESS	MPCX ₂ WIRELESS			
TIMING 13″ High Intensity Red LED Digits Or all White Digits Upgrade	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.			
TEAM SCORES 13" High Intensity Amber LED Digits Or all White Digits Upgrade	Displays 0-199	Displays 0-199	Displays 0-199			
PERIOD 9" High Intensity Amber LED Digits Or all White Digits Upgrade	Displays 0-9	Displays 0-9	Displays 0-9			
NEXT POSSESSION SERVE ADVANTAGE High Intensity Amber LED Digits Or all White Digits Upgrade	Displays arrow for each team.	Displays arrow for each team.	Displays arrow for each team.			
BONUS/DOUBLE BONUS High Intensity Red LED Digits Or all White Digits Upgrade	Displays the letter "B" for each team	Displays the letter ``B`` for each team	Displays the letter "B" for each team			
TIME OF DAY	In place of displaying game time on the scoreboard, the "time out" time may be dis- played or the "time of day". "Time of day" can still display after control turned off.	In place of displaying game time on the scoreboard, the "time out" time may be dis- played or the "time of day". "Time of day" can still display after control turned off.	"Time of day" can display after control turned off.			
HORN Two located in scoreboard	Sounds automatically at 0:00 for a mini- mum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a mini- mum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a mini- mum of two (2) seconds. May omit automatic horn. Can sound manually at any time.			
JUNCTION BOX	Two (2) 4"x2 1/8" with covers, furnished per scoreboard for installation.	N/A	N/A			
CONTROL CABLE	One (1) length required of 2-WIRE (coaxial type) ¼" diameter. Order length required.	N/A N/A				
SEGMENT TIMING	Supported.	Supported. Requires MPCX ₂ segment timer contr				

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.

	#103 Cardinal	#73 Maroon	#102 Team	#99 Golden	#142 Kelly	#74 Forest	#120 Teal	#72 Electronic	#140 Royal	#121 Midnight	#141 Navy	#104 Medium	#70 Desert	#95 Silver	#76 Print
	Red		Orange	Yellow	Green	Green	Blue	Blue	Blue	Blue	Blue	Purple	Tan	Gray	Black
AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA. POWER WITHOUT ETNS: 120 VAC, .60 Amps, 50/60 Hz. / 240 VAC, .30 Amps, 50/60 Hz. / 240 VAC, .30 Amps, 50/60 Hz. Requires earth ground. SCOREBOARD: Size 8'L x 3'H x 8''D (2.44 x .91 x .20 meters), constructed of aluminum. Hanging weight approximately 62 lbs. (28 kg). .30 Amps, 50/60 Hz. Requires earth ground. CAPTIONS: HOME, GUESTS, PERIOD, white 6'' high. (HOME and GUESTS are omitted with ETNs.) POWER WITH ETNS: 120 VAC, .70 Amps, 50/60 Hz / 240 VAC, .35 Amps, 50/60 Hz. Requires earth ground. BUILT-IN LIGHTNING PROTECTION: All models feature optical isolation circuitry providing additional protection against lightning strikes.															
			EW OR R				Г СОРҮ ОІ	F OUR GU	ARANTE	E, PLEAS	E VISIT: I	NEVCO.CO	M/WARR/	ANTY-LIM	ITATION



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT: WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM