





# MODEL 3621

**Size:** 20' x 8' x 8" (6.10 x 2.44 x .20 meters)

**Approximate hanging weight:** 520 lbs. (236 kg) **with ETNs:** 582 lbs. (264 kg)

**Digit Size:** 24"/14" **Digit Color:** High Intensity Red, Amber, or Translucent White



SHOWN WITH OPTIONAL WHITE LEDES



SHOWN WITH OPTIONAL ELECTRONIC TEAM NAMES

### Advanced timing features ideal for combination Football, Baseball, Softball, Soccer, Lacrosse and Field Hockey facilities.

- All the most popular football scoring features on a smaller scoreboard.
- Includes Possession Indicators, Time Outs Left and built-in Horn.
- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.

\* Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

[WWW.NEVCO.COM](http://WWW.NEVCO.COM)

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: [INFO@NEVCO.COM](mailto:INFO@NEVCO.COM)

# INTEGRATED DISPLAY AND SCORING SOLUTIONS



## Model 3621 (Outdoor) Football Scoreboard

### SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 3621	MPC(W)-4/5/6	MPCW-7	MPCX <sub>2</sub> WIRELESS
<b>TIMING</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.
<b>TEAM SCORES</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
<b>QUARTER</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
<b>BALL ON</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
<b>DOWN</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9
<b>YDS TO GO</b> 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99
<b>BALL POSSESSION INDICATORS</b> High Intensity Red, Amber, or Translucent White LED	One for each team shaped in the form of a football.	One for each team shaped in the form of a football.	One for each team shaped in the form of a football.
<b>TIME OF DAY</b>	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	N/A
<b>HORN</b>	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



**AGENCY APPROVAL:** UL/CUL listed, FCC, CE, INDUSTRY CANADA.

**SCOREBOARD:** Size 20'L x 8'H x 8"D (6.10 x 2.44 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Six (6) brackets provided for mounting. Hanging weight approximately 520 lbs. (236 kg) with ETNs 582 lbs. (264 kg).

**CAPTIONS:** HOME, GUESTS, DOWN, YDS TO GO, QTR, BALL ON, white 15" high. (HOME and GUESTS are omitted when ordered with ETNs.)

**LED UNITS:** Seven-bar segmented digits with protective aluminum cover.

**BUILT-IN LIGHTNING PROTECTION:** All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

**POWER WITHOUT ETNS (RED/AMBER):** 120 VAC, 2.9 Amps, 50/60 Hz. / 240 VAC, 1.4 Amps, 50/60 Hz. Requires earth ground.

**POWER WITH ETNS (RED/AMBER):** 120 VAC, 4.1 Amps, 50/60 Hz. / 240 VAC, 2.0 Amps, 50/60 Hz. Requires earth ground.

**POWER WITHOUT ETNS (TRANSLUCENT WHITE):** 120 VAC, 4.9 Amps, 50/60 Hz. / 240 VAC, 2.5 Amps, 50/60 Hz. Requires earth ground.

**POWER WITH ETNS (TRANSLUCENT WHITE):** 120 VAC, 6.0 Amps, 50/60 Hz. / 240 VAC, 3.0 Amps, 50/60 Hz. Requires earth ground.

**GUARANTEE:** TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: [NEVCO.COM/WARRANTY-LIMITATION/](http://NEVCO.COM/WARRANTY-LIMITATION/)  
**U.S. SERVICE: 1-800-851-4040**      **INTERNATIONAL SERVICE: 1-618-664-0360**      **CANADA SERVICE: 1-800-461-8550**



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:  
[WWW.NEVCO.COM](http://WWW.NEVCO.COM)

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360  
 FAX: 618-664-0398 E-MAIL: [INFO@NEVCO.COM](mailto:INFO@NEVCO.COM)