

PATENTED PVBN-6 CABLE-LESS
FLEX-NET PROVIDES 10,000 lbs
TENSILE STRENGTH (PAT. #5,358,257)

SIDELINE ANTENNAE
AND BOUNDARY TAPE
(VBA-80)

ALUMINUM INNER
UPRIGHT TUBE
Ø2-1/2" OD
HEIGHT IS INFINITELY ADJUSTABLE
VIA UNIQUE INTERNAL BEVEL
GEAR ASSEMBLY

WORM DRIVE
GEARBOX WINCH
TIGHTENS NET
(PVBWINCH)

INFINITELY ADJUSTABLE
TELESCOPING STANDARD
UPRIGHT
(PVB600B)

REMOVABLE HANDLE
OPERATE HEIGHT
ADUSTER GEARING
(PVB607I)

ALUMINUM, 10" FLOOR SLEEVE
FOR USE IN WOOD OR SYNTHETIC
PLAYING SURFACES

LOCKABLE HINGED COVER
PLATE AVAILABLE IN
BRASS (PVB-70S) OR
CHROME (PVB-70S-CP) FINISH

STEEL OUTER
UPRIGHT TUBE
Ø3 OD

UPRIGHT PADS, NOT SHOWN
(PVB-60P)

2" VELCRO STRAP TIGHTENS
BOTTOM OF NET WHILE THE
BUCKLE IS PADDED FOR PROTECTION

VELCRO STRAP WRAPS AROUND
BUCKLE FOR SAFETY

SECTION A-A

REV	DESCRIPTION	DATE	INIT
A	CHANGED LOGO	2/14/14	HT

SPECSHEET

PVB-6000
Steel International Net System
Deluxe 3" Aluminium Volleyball
Upright System with Infinitely
Adjustable Height

THIS PRINT IS THE PROPERTY OF JAYPRO SPORTS, LLC
AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION

FAX:
860.444.1779 (SALES)
860.440.0628 (ENG.)



www.jaypro.com

800.243.0533 (TOLL FREE)
860.447.3001 (LOCAL)

PHONE:

DRAWING NUMBER: **PVB-6000**

DRAWN BY: MJE

CHECKED BY: -

ISSUE DATE: 3/19/2010

SHEET: 1 OF 2

REV: A

JAYPRO MODEL PVB-6000

“Steel International Net System” **DELUXE 3” DIAMETER STEEL HEIGHT ADJUSTABLE** **VOLLEYBALL SYSTEM**

System shall consist of two uprights and one winch and shall be supplied fully assembled. Uprights are intended to fit snugly into 3” ID x 10” deep rigid aluminum floor sleeves (model #: PVB-70S/PVB-70S-CP).

Two piece telescoping uprights shall provide infinitely adjustable net height settings from 6’6” to 8’2” by means of an internal bevel gear design. No field assembly required upon receipt. Lower section of upright shall be constructed of 3” OD x 0.219” wall steel tube with a durable black finish. Upper section shall be constructed of 2-1/2” OD x 0.250” wall aluminum tube with 4” diameter pulley to accommodate the net tensioning straps. Anchor strap shall be adjustable and winch strap shall be long enough to readily adapt to varying sleeve installation widths.

Lower upright section shall have a molded composite foot to protect the finished floor during transportation, storage, and installation of standards.

Tensioning winch shall have an internal worm gear construction with an effective 10:1 turn ratio to eliminate snap-back and shall be completely enclosed with a welded steel cover. The winch shall be furnished with folding handle. Winch will have 1-1/2” wide high tensile strength (7700#) nylon strap with sewn snap buckle for complete cable-less design. Winch is located on outside of post for added player safety.

Standard pads: PVB-60P included w/ PVB-6000. Colors shall be available in any of fourteen (14) different colors (red, navy blue, yellow, light blue, grey, black, maroon, kelly green, forest green, royal blue, pink, tan, purple, orange). Color selection available per request.

PVB-6000