

PATENTED PVBN-6 CABLE-LESS  
FLEX-NET PROVIDES 10,000 lbs  
TENSILE STRENGTH (PAT. #5,358,257)

SIDELINE ANTENNAE  
AND BOUNDARY TAPE  
(VBA-80)

ALUMINUM INNER  
UPRIGHT TUBE  
Ø2-1/2" OD  
HEIGHT IS INFINITELY ADJUSTABLE  
VIA UNIQUE INTERNAL BEVEL  
GEAR ASSEMBLY

WORM DRIVE  
GEARBOX WINCH  
TIGHTENS NET  
(PVBWINCH)

INFINITELY ADJUSTABLE  
TELESCOPING STANDARD  
UPRIGHT  
(PVB600B)

REMOVABLE HANDLE  
OPERATE HEIGHT  
ADUSTER GEARING  
(PVB607I)

ALUMINUM, 10" FLOOR SLEEVE  
FOR USE IN WOOD OR SYNTHETIC  
PLAYING SURFACES

LOCKABLE HINGED COVER  
PLATE AVAILABLE IN  
BRASS (PVB-70S) OR  
CHROME (PVB-70S-CP) FINISH

STEEL OUTER  
UPRIGHT TUBE  
Ø3 OD

UPRIGHT PADS, NOT SHOWN  
(PVB-60P)

2" VELCRO STRAP TIGHTENS  
BOTTOM OF NET WHILE THE  
BUCKLE IS PADDED FOR PROTECTION

VELCRO STRAP WRAPS AROUND  
BUCKLE FOR SAFETY

## SECTION A-A

REV	DESCRIPTION	DATE	INIT
A	CHANGED LOGO	2/14/14	HT

### SPECSHEET

**PVB-6000**  
Steel International Net System  
Deluxe 3" Aluminium Volleyball  
Upright System with Infinitely  
Adjustable Height

THIS PRINT IS THE PROPERTY OF JAYPRO SPORTS, LLC  
AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION

FAX:  
860.444.1779 (SALES)  
860.440.0628 (ENG.)



www.jaypro.com

PHONE:  
800.243.0533 (TOLL FREE)  
860.447.3001 (LOCAL)

JAYPRO SPORTS, LLC, 976 HARTFORD TURNPIKE, WATERFORD, CT 06395 USA

DRAWING NUMBER/PART NUMBER:  
**PVB-6000**

DRAWN BY: MJE

CHECKED BY: -

ISSUE DATE: 3/19/2010

SHEET: 1 OF 2

REV: A

# **JAYPRO MODEL PVB-6000**

## **“Steel International Net System”** **DELUXE 3” DIAMETER STEEL HEIGHT ADJUSTABLE** **VOLLEYBALL SYSTEM**

System shall consist of two uprights and one winch and shall be supplied fully assembled. Uprights are intended to fit snugly into 3” ID x 10” deep rigid aluminum floor sleeves (model #: PVB-70S/PVB-70S-CP).

Two piece telescoping uprights shall provide infinitely adjustable net height settings from 6’6” to 8’2” by means of an internal bevel gear design. No field assembly required upon receipt. Lower section of upright shall be constructed of 3” OD x 0.219” wall steel tube with a durable black finish. Upper section shall be constructed of 2-1/2” OD x 0.250” wall aluminum tube with 4” diameter pulley to accommodate the net tensioning straps. Anchor strap shall be adjustable and winch strap shall be long enough to readily adapt to varying sleeve installation widths.

Lower upright section shall have a molded composite foot to protect the finished floor during transportation, storage, and installation of standards.

Tensioning winch shall have an internal worm gear construction with an effective 10:1 turn ratio to eliminate snap-back and shall be completely enclosed with a welded steel cover. The winch shall be furnished with folding handle. Winch will have 1-1/2” wide high tensile strength (7700#) nylon strap with sewn snap buckle for complete cable-less design. Winch is located on outside of post for added player safety.

Standard pads: PVB-60P included w/ PVB-6000. Colors shall be available in any of fourteen (14) different colors (red, navy blue, yellow, light blue, grey, black, maroon, kelly green, forest green, royal blue, pink, tan, purple, orange). Color selection available per request.

**PVB-6000**