



**BASKETBALL**

**ACCESSORIES**

# MODEL SSC-T5



**Size:** 24"L x 24"H x 2"D

**Approximate hanging weight:** 35 lbs. each (includes Indoor Accessory Driver (IAD) box and horns)

**Digit Color:** Super Bright Red & Amber or White

**Digit Size:** Game Time: 5" / Shot Clock Time: 13"

## DESIGN FLEXIBILITY



MODEL ABOVE SHOWN WITH ALL WHITE DIGITS UPGRADE.

**SINGLE SIDED**



Can be mounted to backboard and flush with walls

**DOUBLE SIDED**



Ideal for fans and coaching staff

**3-SIDED**



Optimal viewing angles for players, coaches, and officials

## Advanced timing features ideal for Basketball.

- Displays game time as well as shot clock time.
- Integrates with Nevco End of Period Lights through the IAD box (included with shot clock).
- Bright, long lasting, energy-efficient LEDs reduce power consumption and operating expense.
- Horn is encased in an external box that can be attached above or below the clock, ensuring sound clarity.
- Durable Lexan, yet lightweight, cabinet design can withstand heavy impact from basketball.
- Shot clock connects through cat5 cable to the IAD box, which is easy to conceal and protected from game elements.
- Integrates with Nevco accessories, such as End of Period lights and Locker Room Clocks.
- Daisy chaining capability allows for single or double sided mounting.



MAXIMIZE YOUR IMPACT™

**BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:**  
**WWW.NEVCO.COM**

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360  
FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

# INTEGRATED DISPLAY AND SCORING SOLUTIONS

## Model SSC-T5 (Indoor) Basketball Shot Clock



### SSC-T5 Shot Clock Details

<b>AGENCY APPROVAL</b>	FCC, CE, INDUSTRY CANADA, Power Supply is UL/CUL listed
<b>SHOT CLOCKS</b>	Size: 24"L x 24"H x 2"D Hanging Weight: 35lbs each (including IAD box & horns) Constructed of aluminum
<b>LED UNITS</b>	Seven-bar segmented digits with protective aluminum
<b>POWER</b>	12vDC low voltage power input from included 120 VAC 0.5A Power Supply
<b>BUILT-IN LIGHTNING PROTECTION</b>	All models feature optical isolation circuitry providing additional protection against lightning strikes.

### SHOT CLOCK / CONTROL OPERATING FEATURES

MODEL SSC-T5 (SHOT CLOCK)	MPC WIRED (CONTROL)	MPCW WIRELESS (CONTROL)	MPCX <sub>2</sub> WIRELESS (CONTROL)
<b>GAME TIMING</b> 5" Super Bright Red LED Digits Or all White Digits Upgrade	<ul style="list-style-type: none"> <li>• Bi-directional UP or DOWN count.</li> <li>• Any number can be set between 0:00-99:59.</li> <li>• 1/10th seconds display during final minute.</li> </ul>	<ul style="list-style-type: none"> <li>• Bi-directional UP or DOWN count.</li> <li>• Any number can be set between 0:00-99:59.</li> <li>• 1/10th seconds display during final minute.</li> </ul>	<ul style="list-style-type: none"> <li>• Bi-directional UP or DOWN count.</li> <li>• Any number can be set between 0:00-99:59.</li> <li>• 1/10th seconds display during final minute.</li> </ul>
<b>SHOT CLOCK TIMING</b> 13" Super Bright Amber LED Digits Or all White Digits Upgrade	<ul style="list-style-type: none"> <li>• Any shot time can be set between 0-69 seconds.</li> <li>• Handheld switch provides instant reset to programmed shot time, out of bounds time and prevents timer from counting.</li> </ul>	<ul style="list-style-type: none"> <li>• Any shot time can be set between 0-69 seconds.</li> <li>• Handheld switch provides instant reset to programmed shot time, out of bounds time and prevents timer from counting.</li> </ul>	<ul style="list-style-type: none"> <li>• Any shot time can be set between 0-69 seconds.</li> <li>• Handheld switch provides instant reset to programmed shot time, out of bounds time and prevents timer from counting.</li> </ul>
<b>HORN</b>	<ul style="list-style-type: none"> <li>• Encased in external box that can be attached above or below the clock.</li> <li>• Sounds automatically at 00.</li> <li>• Shot clock violation has unique sound.</li> <li>• End of main time matches scoreboard sound.</li> </ul>	<ul style="list-style-type: none"> <li>• Encased in external box that can be attached above or below the clock.</li> <li>• Sounds automatically at 00.</li> <li>• Shot clock violation has unique sound.</li> <li>• End of main time matches scoreboard sound.</li> </ul>	<ul style="list-style-type: none"> <li>• Encased in external box that can be attached above or below the clock.</li> <li>• Sounds automatically at 00.</li> <li>• Shot clock violation has unique sound.</li> <li>• End of main time matches scoreboard sound.</li> </ul>
<b>SYSTEM OPERATION</b>	<ul style="list-style-type: none"> <li>• Control can operate scoreboard and shot clocks at the same time.</li> <li>• When using shot clocks and scoreboard horns as a system, they sound at the same time.</li> </ul>	<ul style="list-style-type: none"> <li>• Control can operate scoreboard and shot clocks at the same time.</li> <li>• When using shot clocks and scoreboard horns as a system, they sound at the same time.</li> </ul>	<ul style="list-style-type: none"> <li>• Control can operate scoreboard and shot clocks at the same time.</li> <li>• When using shot clocks and scoreboard horns as a system, they sound at the same time.</li> </ul>
<b>INDEPENDENT OPERATION</b>	Control operates shot clocks as an independent system.	Control operates shot clocks as an independent system.	Control operates shot clocks as an independent system.
<b>CONTROL CABLE</b>	<ul style="list-style-type: none"> <li>• Two (2) lengths of 2-WIRE (coaxial type) ¼" diameter required.</li> <li>• Order the lengths required.</li> </ul>	N/A	N/A
<b>SEGMENT TIMING</b>	Supported.	Supported.	Requires MPCX <sub>2</sub> segment timer control.

**GUARANTEE:** TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: [WWW.NEVCO.COM/](http://WWW.NEVCO.COM/)

**U.S. SERVICE:** 1-800-851-4040.

**INTERNATIONAL SERVICE:** 1-618-664-0360.

**CANADA SERVICE:** 1-800-461-8550.



MAXIMIZE YOUR IMPACT™

**BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:**  
**WWW.NEVCO.COM**

**U.S. & CANADA:** 800-851-4040 **INTERNATIONAL:** 618-664-0360

**FAX:** 618-664-0398 **E-MAIL:** [INFO@NEVCO.COM](mailto:INFO@NEVCO.COM)