

SECTION	GROSS	ACTUAL	NO. OF	NET					
LENGTH	SEATS	SEATS	ROWS	SEATS					
55.5	37.00	37.00	1	37					
13.5	9.00	9.00	12	108					
4.5	3.00	3.00	2	6					
3.5	2.33	2.00	2	4					
19.5	13.00	13.00	12	156					
7	4.67	4.00	2	8					
7	4.67	4.00	2	8					
13.5	9.00	9.00	12	108					
3.5	2.33	2.00	2	4					
4.5	3.00	3.00	2	6					
	445								
	6								
TOTAL N	451								
(BASED ON 18" PER SEAT)									

- GENERAL REQUIREMENTS:

 A. THE INSTALLATION OF THE ANGLE FRAME BLEACHER, SHOWN ABOVE, IS DESIGNED TO BE INSTALLED
- DUIDOURS.

 B. INSTALLATION IS TO BE ON A FLAT LEVEL SURFACE WITH EITHER OF THE FOLLOWING CONDITIONS:

 1. CONCRETE PAD WITH A MINIMUM COMPRESSION STRENGTH OF 3000 PSI.

 2. SOIL WITH A MINIMUM SOIL BEARING OF 2000 PSI.

 C. REQUIRED SITE WORK TO MEET THE ABOVE NOTED REQUIREMENTS, IS THE SOLE RESPONSIBILITY OF THE
- OWNER AND TO BE COMPLETED BEFORE MATERIALS SHIP.
- D. OWNER TO LOCATE AND PROTECT UNDERGROUND CONDUIT, PLUMBING, AND/OR OTHER UTILITIES WHERE NEW WORK WILL BE PERFORMED.



This drawing and all information contained herein is the property of NATIONAL RECREATION SYSTEMS, INC. and is not to be reproduced without the express written permission of this manufacturer. We assume no responsibility for unauthorized use of this drawing. NATIONAL RECREATION SYSTEMS, INC. is not responsible for local permits and occupancy requirements.

ì S,	PROJECT/SITE: 36A-1505506CL06_01 SALES									
9	DESCRIPTION: 36" ELEV. 15 ROW x 55'-6" SEATING PLAN									
	DRAWN BY: JCM	DATE: 3/5	5/24 F	REVISION: ()	SCALE: N.T.S.	SHEET NUMBER:	TD.1			

