

— Instruction Manual —

TB200

One Piece 2 3/8" Tetherball System



Customer Service
(800) 247-7668

PARTS LIST					
Item	Qty	Description	Item	Qty	Description
A	1	2 3/8" Tetherball Pole	C	1	Ground Socket (Optional, packaged separately)
B	1	TB50-B Tetherball Assembly (Packaged separately)	D	2	60# Premix Concrete (Customer Supplied)

- ♦ Inspect all contents prior to installation. Report any missing parts to dealer immediately.
- ♦ Read all instructions before proceeding.

Ensure the area around the pole or optional ground socket installation is clear of obstructions. A minimum of 12' diameter around the pole or ground sleeve is recommended.

1. If you intend to permanently install the 2 3/8" *Tetherball Pole* (A) into the ground, dig an 8" diameter by 30" deep hole and proceed to instruction #3. See Figure 1.
2. If you intend to use the optional *Ground Socket* (C) to allow removal of the 2 3/8" *Tetherball Pole* (A) when not in use, follow the instructions provided in the *Ground Socket* (C).
3. Mix the 60# Premix Concrete (D) to relatively dry consistency and fill the hole to within approximately 2" from the top.
4. Insert 2 3/8" *Tetherball Pole* (A) into the center of the concrete agitating it as it is lowered. Ensure the 2 3/8" *Tetherball Pole* (A) extends 10' above the playing surface and is plumb as the concrete cures. See Figure 1.
5. Add 60# Premix Concrete (D) if necessary to fill the remaining void, finish top of concrete and wipe excess concrete from 2 3/8" *Tetherball Pole* (A).
6. Install the TB50-B *Tetherball Assembly* (B) onto the 2 3/8" *Tetherball Pole* (A) using instructions supplied with the TB50-B *Tetherball Assembly* (B) after the concrete is fully cured.

