

Sleeves shall be specifically designed to allow removable and adjustable installation of Bison gooseneck style football goalposts. Sleeves shall consist of an 8" square steel structure with a powder coated finish, a minimum of 50" long with a formed pan, that is welded and hot dip galvanized, attached at the top of the structure to allow for bury below the playing surface. Sleeve design shall allow for rotational goalpost crossbar height adjustment of up to 4" at installation by means of a 2½" diameter threaded adjustable screw located in the bottom of the sleeve to allow exact 10' official crossbar height. Post shall be adjusted plumb by means of four ¾" adjusting screws. An anti-rotation device shall hold the goalpost square to the field. An aluminum finish cap shall fill the sleeve pan both when the goal is installed and when it is removed. Specify whether sleeve is used for 4½" OD (FB45S) or 5 9/16" OD (FB55S) goalposts. Installations to be completed in accordance to manufacturer's instructions. Do not scale drawings. Shipping weight shall be 120# (FB45S) and 125# (FB55S) each.

MANUFACTURED BY BISON, INC. • 603 L STREET, LINCOLN, NEBRASKA, 68508 • WWW.BISONINC.COM • 402-474-3353 PROTECTED BY COPYRIGHT • ALL RIGHTS RESERVED • SUBJECT TO CHANGE WITHOUT NOTICE • REVISED 03/05/2015