

CROWDSTOPPER

PRODUCT SPECIFICATIONS

Vinyl-coated Barricades

Overall Length:	8' 6" (8' 3" when interlocked)
Overall Height:	43"
Weight:	Bridge Foot Style – 38 lbs; Flat Foot Style – 40 lbs
Material:	Steel
Main Frame:	Outside perimeter (main frame) is made of 1½" O.D. steel tubing, minimum 16 gauge. The outer frame is a single length of tubing without welds or deformation. Pipe is bent at right angles with a minimum of smooth deformation. Horizontal and vertical bars are at right angles to overall frame.
Grill:	21 equally-spaced bars inside vertical members, made of ½" O.D. steel tubing, minimum 16 gauge. Minimum of ½" weld at the top and at the bottom of each upright bar. 21 interior bars are ¼" apart, O.D. to O.D. The spacing between inside vertical members does not exceed 4½" and meets all standard codes.
Locking:	Male-Female interlocking ends. Units join and unlock at one position (30 degrees). Male interlocking device is a minimum ⅝" diameter rod welded through main frame at both ends. Male/Female connections have enough clearance to allow for uneven ground, a minimum of ½" on top and bottom when connected.
Feet:	Two (2) bolt on flat feet ½" x 2" flat steel bar with ¼" O.D. 14 stem, or, two (2) bolt on bridge feet 1½" O.D. steel, 16 gauge, with ¼" O.D. stem.
Finishes:	PVC Vinyl-Coated Black and Orange. Custom colors available
Warranty:	3-year warranty against manufacturer's defects.

