



SPECIFICATIONS ON OPPOSITE SIDE.



15 OZ VINYL

01 Light Blue




02 Royal Blue



03 Red



04 White



05 Orange



06 Yellow




08 Tan




09 Gray



10 Maroon



11 Purple



12 Black



13 Navy Blue



14 Kelly Green



15 Dark Green



15 OUNCE, DOUBLE-COATED LAMINATED VINYL

porter[®]
www.PorterAthletic.com



Fabric Specifications

Total Weight: 15oz/yd²

Testing Method: ASTM D3776

Base Fabric:

9 x 9 x 500 Denier Polyester

Grab Tensile (lb/in): 236(w) x 219(f)

Testing Method: ASTM D751

Trapezoidal Tear (lb): 65(w) x 43(f)

Testing Method: ASTM D751

Adhesion (lb/in): 16(w) x 23(f)

Testing Method: ASTM D751

Cold Crack, 3/8" Mandrel: -50° C

Testing Method: ASTM 2136

porter®

150Z VINYL

DOUBLE-COATED, LAMINATED

Porter uses a heavy-duty 15oz vinyl on all our standard pads. The durable leather embossed finish is tear & abrasion resistant. Available in 14 UV resistant stock colors to compliment and coordinate with any school colors.

Features:

- Tear & Abrasion Resistant
- Rot & Fungus Resistant
- Mildew Resistant
- Dimensionally Stable
- Shrink Resistant
- UV Resistant



Flame Retardancy

NFPA 701-2010 TM2: Pass

ASTM E84: Class A or Class 1

CA Title 19-1237.1: Pass

CAL/ULC-S 109-03 LG & SM: Pass



Composition

Lead: Pass

Testing Method: GREENGUARD Certified

Phthalates: Pass

Testing Method: GREENGUARD Certified



Applications Include:

- Indoor/Outdoor Wall Padding
- Stage Padding
- Indoor/Outdoor Column Padding
- Indoor/Outdoor Sewn Padding
- "I" Beam Padding
- Corner Padding
- Pole Padding
- Portable Backstop Badding
- Gymnasium Mats